

Cat[®] ELC[™]

Extended Life Coolant for Caterpillar and original equipment manufacturer (OEM) diesel and gasoline engines.

50/50 Premix



Recommended Use

Cat ELC meets or exceeds the requirements of the following specifications:

- Cat EC-1
- TMC RP-329
- TMC RP-338
- ASTM D-3306
- ASTM D-6210
- SAE J1034

Cat ELC also meets the performance requirements of Cummins, Detroit Diesel, International, Mack and Volvo.

Discover the Difference

Cat ELC is developed, tested and approved by Caterpillar to meet the same high standards as Genuine Cat Parts.

Factory-Fill—Used as standard factory-fill for all Cat machine cooling systems.

Lower Maintenance Costs—Reduces engine coolant and additive costs by as much as 500% compared to conventional coolants. It eliminates the need for supplemental coolant additives, extends coolant change-out intervals and reduces disposal requirements.

Advanced Metal Protection—Incorporates an advanced formula technology with organic acid additive corrosion inhibitors, such as a combination of mono and dicarboxylates for maximum protection of copper, solder, brass, steel, cast iron and aluminum.

Caterpillar. The difference counts.™

Cat Dealers define world-class product support. We offer you the right parts and service solutions, when and where you need them.


The Cat Dealer network of highly trained experts keeps your entire fleet up and running to maximize your equipment investment.

CATERPILLAR[®]

Cat ELC


Cat ELC for Maximum Coolant Life

Cat DEAC™

 **3000 Hour Life or 333,000 km (200,000 miles)**


Cat Supplemental Coolant Additives Every 250 Hours or 25,000 km (15,000 miles)

Cat ELC (Machines and Commercial Engines)

 **12,000 Hour Life or 6 Years***
(whichever comes first)

Cat Extender Every 6000 Hours

Cat ELC (Truck Engines)

 **1,000,000 km (600,000 miles) or 6 Years***
(whichever comes first)

Cat Extender Every 500,000 km (300,000 miles)

* These coolant change intervals are only possible with annual S•O•S Level 2 coolant sampling and analysis.

Cat ELC Extender for Longer Life

- Exceeds Cat EC-1 performance requirements
- Protects against cylinder liner/block pitting and cavitation erosion
- Should be added at 500,000 km (300,000 miles) for Cat powered on-highway trucks and 6,000 hours for commercial engines
- Extender is only necessary once during the life of the coolant
- Ensures Cat ELC performance to 1,000,000 km (600,000 miles) or 12,000 hours

Available Pre-Mixed or in Concentrate

Cat ELC 50/50 Premix is provided in standard English and metric container sizes. Cat ELC Concentrate is only available in 1 gallon cans for radiator top-off. Coolant Conditioner and ELC Dilution Test kits are also available.

ELC Extender and Flush Intervals

Cat ELC Extender should be added after 6,000 hours or 300,000 miles (500,000 km) of operation, and the system should be drained and flushed with clean water after 12,000 hours or 600,000 miles (1,000,000 km). No cleaning agents are needed. If S•O•SSM Services are used regularly, safe operation with Cat ELC may extend beyond 12,000 hours.

Typical Characteristics*

Color	Strawberry Red
Boiling protection with 15 psi (1 bar) radiator cap	
50% Cat ELC/50% water	129°C (265°F)
60% Cat ELC/40% water (ELC concentrate added)	132°C (270°F)
Freezing protection	
50% Cat ELC/50% water	-37°C (-34°F)
60% Cat ELC/40% water (ELC concentrate added)	-52°C (-62°F)
Nitrite (50% solution)	500 ppm
Molybdate (50% solution)	530 ppm

*The values shown are typical values and should not be used as quality control parameters to either accept or reject product. Specifications are subject to change without notice.

S•O•S Services for early problem detection

Protect your investment with Cat S•O•S Coolant Analysis, the ultimate detection and diagnostic tool for your engines. We recommend S•O•S Level 1 Coolant Analysis according to the engine's Operation and Maintenance Manual, or Level 2 Coolant Analysis annually for all your Cat equipment.

Cat Filters: Complete protection for your machine

Combine Cat Fluids with Cat Filters for the highest level of contamination control and protection for your machine. We recommend Cat Filters for all Cat machine applications.

Health and Safety

For information on proper use for health, safety, and environment, please refer to the Material Safety Data Sheet (MSDS). Read and understand the MSDS before using this product. Always observe good hygiene measures. For a copy of the MSDS, contact us or visit the web at www.catmsds.com.

CATERPILLAR®